

Boring Log


Client:
Project:
Street:
City/Co./State:

Boring #: **MW-10**
Date:
Project #:

From (ft)	To (ft)	Soil Classification (USCS)	Sampling Time	Recovery (ft)	TOV Reading (ppm)
0	5	Ground Surface: Asphalt HAND AUGER: to 5 feet bgs. Orange, silty CLAY (CL) - Dry	NA	NA	0.1
5	10	Yellowish-tan, coarse grained SAND (SM) with some silt - Dry	NA	85%	2.2
10	15	Yellowish-tan, silty SAND (SM) - Moist	11:20	100%	3.9
15	20	Orange with black striations, silty, fine grained SAND (SM) with some clay - Moist	NA	95%	2.3
20	25	Soft, orange, silty SAND (SM) - Moist	NA	95%	2.2
25	30	Orange, fine grained SAND (SM) with some silt - Moist	NA	100%	2.1
		Boring Terminated at 30 feet bgs.			

Terminated at: **30 feet bgs**
Groundwater : **Groundwater at approximately 12 feet bgs.**

Remarks:	TOV = Total Organic Vapors NA= Not Applicable / Not Analyzed bgs= Below Ground Surface	Converted to Well: Yes Well Number: MW-10
----------	----------------------------------------------------------------------------------------------	------------------------------------------------------------

Scientist Driller: Drilling Method: Outer Casing NA Drilling Method: Inner Casing Geoprobe 7822DT Sampling Method: 5-foot, macro-core sampler w/ PVC liner (soil) TOV Instrument: Photo Ionization Detector (PID)	<p style="text-align: center;"><u>Laboratory Samples</u></p> Soil: Yes Depth(s): 10'-15'  denotes sample selected for laboratory analysis. Water: Yes 9/30/2011
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------